

H-32



> HIGHLIGHTS



Windows Embedded Compact 7

2.8" QVGA touch screen



Bluetooth V2.1 + EDR



WiFi, IEEE 802.11 a/b/g/n



USB, OTG

IP 54

1.5 meter drop proof

H-32

> BASIC PRODUCT SPECIFICATIONS

OPERATION

CPU: AM3354 ARM Cortex A8, 800 MHz **O/S:** Windows Embedded Compact 7

SOFTWARE: Wordpad, Internet Explorer, Active Sync, Opticon scanner application, Upgradeable via integrated microSD card slot **RTC:** Supports year, month, day, hour, minute, second (leap year supported)

MEMORY

NAND FLASH: 256 MB **RAM:** 256 MB mobile DDR2 **EXPANSION:** User accessible MicroSDHC

DISPLAY

TYPE: Transflective QVGA with touch panel, with white LED backlight **SIZE:** 2.8", 240 x 320 pixels **MODE:** Portrait

OPERATING INDICATORS

VISUAL: 2 LEDs (red/green scanning indication & charging indicator) **NON-VISUAL:** Vibrate, Speaker

OPERATING KEYS

ENTRY OPTIONS: 26 keys total, 12 key (alpha)numeric keypad, 4-way navigation keys, function key, backspace key, power key, Enter key, Alpha key, Escape key, Shift key, 3 scan keys,

COMMUNICATION

USB: Micro USB OTG, ver. 2.0 **BLUETOOTH:** Ver. 2.1 + EDR **W-LAN:** 802.11 a/b/g/n; WEP, WPA, WPA2; WEP, TKIP, AES; Static (40 and 128 bit), PSK (Pre-Shared), Dynamic; EAP, PEAP, LEAP; Cisco CCX version 4 **AUDIO:** Speaker **EXTENSION:** User accessible microSD I/O

POWER

RECHARGEABLE BATTERY: Lithium-Ion 3.7V 1800mAh (sold separately) **BACKUP BATTERY:** fixed rechargeable Lithium-Ion 15mAh **CHARGING METHOD:** Through Micro USB cable (enclosed item), power supply (sold separately) or cradles (sold separately)

BARCODE SCANNER OPTICS

LIGHT SOURCE: 650 nm visible laser diode **SCAN RATE:** 100 scans/sec **READING PITCH ANGLE:** -35 to 0°, 0 to +35° **READING SKEW ANGLE:** -50° to -8°, +8° to +50° **READING TILT ANGLE:** -20° to 0°, 0° to +20° **CURVATURE:** R>15 (EAN8), R>20 (EAN13) **MIN. PCS VALUE:** 0.45 **DEPTH OF FIELD:** At PCS 0.9, Code 39, 70 - 650 mm / 2.76 - 25.59 in (1.00 mm / 39 mil), 50 - 420 mm / 1.97 - 16.54 in (0.5 mm / 20 mil), 50 - 260 mm / 1.97 - 10.24 in (0.25 mm / 10 mil), 50 - 150 mm / 1.97 - 5.91 in (0.15 mm / 6 mil), 60 - 120 mm / 2.36 - 4.72 in (0.127 / 5 mil)

SUPPORTED SYMBOLOGIES

BARCODE (1D): JAN/UPC/EAN incl. add on, Codabar/NW-7, Code 11, Code 39, Code 93, Code 128, GS1-128 (EAN-128), GS1 DataBar (RSS), IATA, ISBN, Industrial 2of5, Interleaved 2of5, Matrix 2of5, MSI/Plessey, Telepen **POSTAL CODE:** Chinese Post, Korean Postal Authority code **2D CODE:** Composite Codes, MicroPDF417, PDF417

DURABILITY

TEMPERATURE IN OPERATION: -10 to 50°C / 14 to 122°F **TEMPERATURE IN**

STORAGE: -20 to 60°C / -4 to 140 **HUMIDITY IN OPERATION:** 20% to 80% RH

HUMIDITY IN STORAGE: 20% to 90% RH **DROP TEST:** 1.5 m / 5 ft drop onto concrete surface **PROTECTION RATE:** IP 54

PHYSICAL

DIMENSIONS (W X H X D): 64 x 143 x 28 mm / 2.52 x 5.63 x 1.1 in **WEIGHT BODY:**

Ca. 195 g / 6.9 oz (incl. battery) **CASE:** Black

REGULATORY & SAFETY

PRODUCT COMPLIANCE: CE, FCC, RoHS, IEC 60825-1 Class 2, FDA CDRH Class II

ENCLOSED ITEMS

USB CABLE, HAND STRAP, QUICK START GUIDE, STYLUS + CORD

SOLD SEPARATELY

POWER SUPPLY: 5V 1A, with EU, US plug, **STANDARD BATTERY:** 3.7V 1800mAh

CRD-32: Single USB cradle, communication & charging **CRD-32-E5:** Multi-cradle, 5 slots, Ethernet communication, charging **HOLSTER**